

BANG & OLUFSEN





SPECIFICATIONS

Tweeter Dome
Tweeter
Midrange Cone
Midrange Diameter
Woofer Cone
Woofer Diameter
Dimensions grill
Frequency Response
Impedance Minimum

Sensitivity
Depth
Cutout Dimension(s)

Recommended Amplifier Power

BOP LCR66

Silk DPSD 1" (25mm) -

Glass Dual 6 1/2" 7.875" x 15.563" (200 x 395mm) 55Hz-20kHz

3.75" (95mm)

6 ohm 25 watts - 150 watts 90dB +/- 3dB

6.625" x 14.375" (168 x 364mm)

BOP THTR66

Silk DPSD 1" (25mm) Glass

6.5" (165mm)

Glass

Quad 6 1/2" (165mm) 8.875" x 30.125" (225 x 765mm)

40Hz-20kHz

6 ohm 10 watts - 200 watts

92dB +/- 3dB 3.75" (95mm)

Magnetic Grille

7.87" x 29" (200 x 737mm)

FEATURES

2-way system

Dual-woofer driver gives better bass

EQ Adjustments

X-Wave™ Woofer Surround

Progressive Suspension

Compression Molded Woofer Baskets

Spring-lock™ 2.0 tool less installation

Magnetic Grille

True 3-way system

Quad woofer driver gives deep and power full bass

EQ Adjustments

X-Wave™ Woofer Surround

Progressive Suspension

Compression Molded Woofer

Spring-lock™ 2.0 tool less installation